



Mark 10 Powerline

MARK 10 POWERLINE VEZ2S5435M

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting – anywhere dimming is required.

Product data

| General Information | |
|-------------------------------|----------------------|
| Lamp Type | F54T5/HO |
| Number Of Lamps | 2 piece/unit |
| Ballast Type | Dimmable Fluorescent |
| Base Model | VEZ2S54 |
| Suitable For Outdoor Use | Yes |
| Automatic Restart | Yes |
| | |
| Operating and Electrical | |
| Input Voltage | 277 V |
| Input Frequency | 60 Hz |
| Total Harmonic Distortion USA | 10 % |
| Power (Rated) (Nom) | 54 W |
| Ignition Method | Programmed Start |
| Crestfactor (Nom) | 1.7 |
| Ignition Time (Nom) | 1.5 s |
| Ballast Factor (Max) | 1 |
| Ballast Factor (Min) | 0.03 |
| Power Factor (Nom) | 0.98 |
| Input Current (Nom) | 0.45 A |

| Input Power (Max) | 125 W |
|--|-----------------|
| Input Power (Min) | 24 W |
| Rated Lamp Power | 54W W |
| | |
| Wiring | |
| Color Input Terminals | Black and White |
| Color Output Terminals | RED, YEL & BLU |
| Wire Striplength | 0.375 mm |
| Control Wire Gauge | NA |
| Lamp Connection | Series |
| Wire Length By Color | No wires |
| Wire Gauge (Nom) | 18AWG mm |
| Wire Type | Solid |
| Remote Wiring Configuration Allowed | No |
| Tandem Wiring Configuration Allowed | No |
| Through Wiring Configuration Allowed | Yes |
| Max Ballast-Lamp Distance Remote Wiring | No Remote |
| Max Ballast-Lamp Distance Tandem Wiring | No Tandem |
| Max Ballast-Lamp Distance Through Wiring | Blue = 5' |
| · | |


Datasheet, 2017, February 1 data subject to change

Mark 10 Powerline

| Connector Type | Poke-In |
|--------------------------|---|
| | |
| Temperature | |
| T-Case Maximum (Nom) | 70 °C |
| Mechanical and Housing | |
| Housing Material | Metal |
| Housing | D |
| Housing Dimensions | 16.7" x 1.18" x 1.0" |
| Approval and Application | |
| EMC Immunity Standard | FCC Consumer |
| Approval Marks | CSA certificate UL certificate CEC Listing RoHS |
| | Compliant |

| Hum And Noise Level | A | |
|---------------------------------|------------------------------|--|
| UL Recognized | No | |
| Desduct Date | | |
| Product Data | | |
| Order product name | MARK 10 POWERLINE VEZ2S5435M | |
| EAN/UPC - Product | 781087109625 | |
| Order code | 913700501471 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 12 | |
| Material Nr. (12NC) | 913700501471 | |
| Net Weight (Piece) | 413.000 g | |
| | | |

Dimensional drawing



| Product | A1 | A2 | B1 | C1 |
|------------------------------|----------|----------|---------|---------|
| MARK 10 POWERLINE VEZ2S5435M | 16.70 in | 16.34 in | 1.18 in | 1.00 in |

