



**PRODUCT FEATURES**

- HID Replacement for Applications from 50 - 150 Watts
- Suitable for Total Enclosed Fixture
- IP64 Rating
- 100-277 Voltage Rating
- Can Be Used in Base Up or Base Down Applications
- 50,000 Hour Lifetime Rating
- UL Type B / DLC 4.4 Certified
- 5-Year Limited Warranty

**PRODUCT SPECIFICATIONS**

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	BASE	BEAM ANGLE
CLC5-10W-5K-E26	10	1250	5000	Ø2.36 x 5.63	E26	360°
CLC1-12W-RE-E26 *	12	1740	5000	Ø2.36 x 4.92	E26	360°
CLC5-14W-5K-E26	14	1750	5000	Ø2.76 x 5.75	E26	360°
CLC1-18W-RE-E26 *	18	2600	5000	Ø2.36 x 5.71	E26	360°
CLC5-22W-5K-E26	22	2750	5000	Ø2.76 x 7.32	E26	360°
CLC6-27WD-E26 5000K	27	3780	5000	Ø3.66 x 7.99	E26	360°
CLC1-27W-RE-E26 *	27	3900	5000	Ø2.36 x 6.69	E26	360°

\* Reduced Envelope

